

# Red Copper Cable Lug Terminal Wire Nose Fitting 5A To 1000A OT

### **Basic Information**

Place of Origin: china Brand Name: jinshunlai

Certification: ISO, AISI, ASTM, GB, EN, DIN

Model Number: 0.1mm-900mm

Minimum Order Quantity: 1kg

• Price: Contact Us

Packaging Details: Waterproof Paper, Steel Strip Packed and

other Standard Export Seaworthy Package,

or customized package

• Delivery Time: 5day

Payment Terms: L/C, T/T, Western Union

• Supply Ability: 90000ton



# **Product Specification**

• Chemical Composition: Cu-Ni Corrosion Resistance: Excellent 8.9 G/cm3 • Density: • Electrical Conductivity: ≤20%IACS 30-40% . Elongation: Formability: Good · Hardness: High . Heat Treatment: Annealing Machinability: Good

Melting Point: 1453-1475°C
Name: Copper Connector
Tensile Strength: 400-550 MPa
Thermal Conductivity: 50-70 W/mK
Weldability: Good

Yield Strength: 200-350 MPa



# More Images



# **Product Description**

# 5A to 1000A OT wire nose red copper terminal blocks fitting extrusion open brass nose wire connectors

#### Other attributes

Place of Origin	Jiangsu, China
Brand Name	jinshunlai
Model Number	PWR
Material	T2
Thickness	3-50mm
Welding	10-200mm
OEM	Accepted
Purity	99.9%
Туре	Copper foil connector
copper foil	120*0.2M
Name	High Quality Flexible Laminated Copper Shunt

### Packaging & delivery

Package Type:	3000a flexible laminated copper busbar Plastic bags ,blister card ,standard
	export cartons

### **Supply Ability**

Supply Ability	1000 Piece/Pieces per Week
----------------	----------------------------

# **Product details**

**Product Description** 

laminated copper foil connector is an excellent electrical conductor,

the laminated copper foil connectors are normally used in new-energy vehicles, switchgear industries, power plants, cathodic protection, bus ducts, transformer, vacuum circuit breaker, resistance welding engineering, electric locomotives and furnaces, etc.

**Detailed Images** 











32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China